

20 19 18 17 16 15 14 13 12 11 9 8 7 6 5 4 3 2 1

VIEW ON MATING SIDE

○	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C		
△	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
○	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1									

A = 32 STANDARD CONTACTS L = 3
 B = 32 STANDARD CONTACTS L = 3
 C = 32 STANDARD CONTACTS L = 3
 S = 96 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G3/O = CONTACT AREA LEVEL 3 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 6 (HIGH TEMPERATURE)

C	G3/O	c1-32
B	G3/O	b1-32
A	G3/O	a1-32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. I 2004-XXXX DRAWN/S 09/09/03 CHK'G/L 09/09/03 APPR'G.L. 09/09/03	QUALITY SYMBOLS MAJOR \blacktriangledown CRITICAL ∇	GENERAL TOLERANCES: (UNLESS SPECIFIED)		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION <input type="checkbox"/> INCH <input type="checkbox"/> METRIC	DIMENSIONS:		SHT	REV		
							<input type="checkbox"/> INCH <input type="checkbox"/> METRIC	<input checked="" type="checkbox"/> METRIC ONLY	REVISE ON CAD ONLY			
		4 PLACES	± 0.1	± 0.15	DRAWN BY & DATE		S.S. 22/05/01	TITLE: 96 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C CONTACTS ARRANGEMENT (HIGH TEMPERATURE)				
		3 PLACES	± 0.1	± 0.15	CHECKED BY & DATE		G.L. 22/05/01	MATERIAL NO. 85003-7005		DRAWING NO. SD-85003-7005		SHEET NO. 1 OF 1
2 PLACES	± 0.1	± 0.15	APPROVED BY & DATE		G.L. 22/05/01		CAD FILENAME		SD-85003-7005.S0			
1 PLACE	± 0.1	± 0.15	ANGULAR \pm		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		MATERIAL NO. 85003-7005		DRAWING NO. SD-85003-7005			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS												

19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1