

## DVI Connectors

1 - 2 3 4 5 6 - 7 8 9 10

### Specification

(DIS) DVI-I Single Link (DDS) DVI-D Single Link  
(DID) DVI-I Dual Link (DDD) DVI-D Dual Link

\* For digital and analog, please choose DVI-I  
\* For digital only, please choose DVI-D

### Number of Contacts

19, 23, 25, 29... Contacts  
Ex. 19 Pin = (19)

### Connector Body (Style)

> For Receptacle > For Overmolded with Cable  
(P) Front Fastened (A) With Strain Relief

### Connector (Housing) Gender

(M) Male Connector (F) Female Connector

### Contact Gender

(M) Male (F) Female

### Assemble Style

> For Receptacle > For Overmolded with Cable  
(S) Solder Type (M) Overmolded with Cable

### Mating Style

(S) Screw Thread

### Backshell

> For Receptacle > For Overmolded with Cable  
(L) Straight / Without Board Lock (L) Straight

### Waterproof Rating

(7) IP 67  
(8) IP 68

### More Information

> For Receptacle > For Overmolded with Cable  
(001), (002)..... (□)+(■) : Cable Type + Cable Length  
Without Cable : Different Versions EX. (A01) = UL20276 Cable + 1M

(□) : Cable Type (■) : Cable Length  
(A) UL20276 From 1M to 5M  
28AWG/PVC EX. (01) = 1M