

External SAS Cable, 4 Lane - mini-SAS (SFF-8088) to 4xInfiniband (SFF-8470), 3M (10-ft.)

MODEL NUMBER: \$520-03M



Highlights

- Hi-Performance 3 Meter SAS
 External Cable
- Mini-SAS SFF-8088 (iSAS) to SFF-8470

System Requirements

 SAS Controllers, SAS Chassis, SAS/SATA Hard Drives

Package Includes

 3 Meter SAS External SFF-8088 to SFF-8470 Cable

Description

Tripp Lite's S520-03M External SAS Cable features "mini-SAS" SFF-8088 to SFF-8470 connectors with heavy- duty metal backshells. This 4-channel cable is constructed with a high-performance Infiniband cable, which features individually shielded parallel pairs, double EMI/RFI shielding and 6.0 Gigabytes per second performance.

Features

- External SAS Cable, Mini-SAS SFF-8088 (iSAS) to SFF-8470 3 Meter
- Made with High-Performance Infiniband Cable
- Supports data transfer rates from 3.0 up to 6.0 gigabytes per second
- SFF-8470 thumbscrew type connector and SFF-8088 connector in die cast zinc housing for durability
- · RoHS compliant

Specifications

OVERVIEW	
UPC Code	037332151964
Technology	SAS
INPUT	
Cable Length (ft.)	9.8
Cable Length (m)	3





PHYSICAL		
Shipping Dimensions (hwd / in.)	8.000 x 10.000 x 0.500	
Shipping Dimensions (hwd / cm)	20.32 x 25.40 x 1.27	
Shipping Weight (lbs.)	0.6600	
Shipping Weight (kg)	0.30	
Color	Black	
CONNECTIONS		
Side A - Connector 1	SFF-8088	
Side B - Connector 1	SFF-8470	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies