


NOT for Patient-Care Rooms - UL1363 Hospital-Grade Surge Protector with 6 Hospital-Grade Outlets, 15 ft. Cord, 1050 Joules

MODEL NUMBER: **SPS-615-HG**



Highlights

- 6 hospital-grade outlets
- 1050 joule rating
- 15-ft. cord with molded hospital-grade plug
- All metal housing

Package Includes

- SPS-615-HG Surge Suppressor
- Instruction manual with warranty information

Description

Tripp Lite's SPS-615-HG offers 15A-capacity AC surge suppression and power distribution in a rugged all-metal outlet strip for 120V applications. Offers 6 AC outlets, 15-ft. AC power cord, built-in resettable circuit breaker and 1050-joule AC surge suppression. Features safety-enhanced hospital grade plug and outlets. Switch safety cover prevents accidental shutoff. Optional use keyhole mounting tabs. 15A circuit breaker controls power to all outlets and protects against overloads. LED indicator verifies line power available. PLUG/OUTLETS: NEMA 5-15PHG Hospital-Grade Plug and 6 x NEMA 5-15RHG Hospital-Grade AC Outlets

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet surge suppression strip

SUPPRESSION: AC: 150V RMS Clamping/1050 joules

Features

- 1050-joule AC surge suppression rating
- Rugged all-metal housing withstands years of use without loss of ground path continuity
- 6 NEMA5-15R Hospital-Grad AC outlets
- 15-ft. AC cord with integrated, molded Hospital-Grade NEMA 5-15PHG plug
- Keyhole mounting tabs and flanges
- Switch safety cover prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120 volt, 50/60Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)
- UL1449 3rd Edition listed
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required



Specifications

| OVERVIEW | |
|------------------------------------|--|
| UPC Code | 037332100085 |
| OUTPUT | |
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles | (6) 5-15R-HG |
| Output (Watts) | 1800 |
| Circuit Breaker (amps) | 15 |
| Transformer Accommodation | Supports 1 large transformer plug accessories without covering remaining outlets |
| Right-Angle Outlets | No |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Input Connection Type | NEMA 5-15P-HG Hospital-Grade |
| Input Cord Length (ft.) | 15 |
| Input Cord Length (m) | 4.57 |
| Voltage Compatibility (VAC) | 120 |
| Maximum Surge Amps | 19500 |
| Right-Angle Plug | No |
| USER INTERFACE, ALERTS & CONTROLS | |
| Diagnostic LED Details | LINE POWER PRESENT (green) |
| SURGE / NOISE SUPPRESSION | |
| AC Suppression Joule Rating | 1050 |
| AC Suppression Response Time | < 1 ns |
| Protection Modes | Includes full normal mode surge suppression |
| Clamping Voltage (RMS) | 140 |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | No |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| PHYSICAL | |
|-------------------------------------|---|
| Shipping Dimensions (hwd / in.) | 14.80 x 2.20 x 6.30 |
| Shipping Dimensions (hwd / cm) | 37.59 x 5.59 x 16.00 |
| Shipping Weight (lbs.) | 2.90 |
| Shipping Weight (kg) | 1.32 |
| Unit Dimensions (hwd / in.) | 1.5 x 13.75 x 2.5 |
| Unit Dimensions (hwd / cm) | 3.81 x 34.9 x 6.35 |
| Unit Weight (lbs.) | 3.20 |
| Unit Weight (kg) | 1.45 |
| Material of Construction | Metal |
| Integrated Keyhole Mounting Tabs | Includes keyhole mounting tabs and flanges |
| Receptacle Color | White |
| Color (AC Line Cord) | Gray |
| CERTIFICATIONS | |
| UL1449 3rd Edition (AC Suppression) | UL1449 3rd Edition (Series Number: AGIB12015SL) |
| UL1363 (Power Tap) | UL1363 (Series Number: AGIB12015SL) |
| cUL / CSA (Canada) | cUL (Series Number: AGIB12015SL) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>